

FONTAINE NO-SLACK

6000PML

Standard/Moderate duty applications Adjustable plate mount

Standard/Moderate duty
On highway only
50,000 lbs vertical load
150,000 lbs drawbar pull
Approx top plate weight 205 lbs

Mounting Bracket

Fontaine PML Adjustable Plate Mount

- Two-inch adjustment increments give you greater versatility for improved payload distribution
- Computer design technology cuts excess weight without sacrificing one pound of capacity
- New greaseless bracket liner gives you consistent lubrication, reduces wear (no metal-to-metal contact) and cuts maintenance costs
- Dual durometer two-piece bushing for improved shock absorption and better support
- Computer designed cast bracket for lighter weight and greater strength
- Brackets are welded to a 3/8" steel plate that has six bolt holes on each side

Top Plate

Fontaine No-Slack® 6000 Series Stamped Steel

- No-Slack lock self-adjusts to accommodate kingpin wear
 - Switch from trailer to trailer hassle-free
 - Snug, secure connection
 - Reduces shock inputs into frame when braking/accelerating
 - Improves driver comfort
 - Reduces driver complaints
 - Extends service life of components
- Locking trigger helps minimize high-hitching
 - Reduces driver frustration
 - Reduces tractor, trailer and tire damage
 - The industries best defense against false coupling
 - Saves expensive wrecker and clean up bills
- Easy coupling force—only 30 lbs!
 - Less wear and tear on the kingpin
 - Extends service life of drivetrain components
- Pull handle is the easiest to operate in the industry
 - Opens easily with a simple, straight pull of the handle
 - No complicated opening sequence to remember

Top Plate Performance Options

■ Air actuated – In-cab air release valve located on the dash opens the fifth wheel lock only when the tractor parking brakes are set.



www.fifthwheel.com • 800-874-9780 • Email: parts@fifthwheel.com