

# Blocked (No-Tilt) Fifth Wheels

## BLH7AWB blocked air slide fifth wheels (Tilt/No-Tilt Option)

**Part Number Mounted Height\* Description**  
 BLH7AWB7PT . . . 7-3/4" . . . Blocked H7 top plate with Blocked AWB bracket  
 BLH7AWB8PT . . . 8-3/4" . . . Blocked H7 top plate with Blocked AWB bracket  
 BLH7AWB9PT . . . 9-3/4" . . . Blocked H7 top plate with Blocked AWB bracket  
 BLH7AWB10PT . . 10-3/4" . . . Blocked H7 top plate with Blocked AWB bracket  
 Note: Does not include slide rails.



Removing blocking bar converts "No-Tilt" blocked fifth wheel to standard fifth wheel that can tilt.

### Blocked Complete Assemblies

H7 Blocked AWB Part Number	Fifth Wheel Height*	Slide Length	Weight	H7 Blocked AWB Part Number	Fifth Wheel Height	Slide Length	Weight
BLH7AWB775012	7-3/4"	12"	602 lbs	BLH7AWB975012	9-3/4"	12"	620 lbs
BLH7AWB775016		16"	610 lbs	BLH7AWB975016		16"	628 lbs
BLH7AWB775024		24"	622 lbs	BLH7AWB975024		24"	640 lbs
BLH7AWB775036		36"	642 lbs	BLH7AWB975036		36"	660 lbs
BLH7AWB775048		48"	669 lbs	BLH7AWB975048		48"	687 lbs
BLH7AWB875012	8-3/4"	12"	611 lbs	BLH7AWB1075012	10-3/4"	12"	643 lbs
BLH7AWB875016		16"	619 lbs	BLH7AWB1075016		16"	651 lbs
BLH7AWB875024		24"	631 lbs	BLH7AWB1075024		24"	663 lbs
BLH7AWB875036		36"	651 lbs	BLH7AWB1075036		36"	683 lbs
BLH7AWB875048		48"	678 lbs	BLH7AWB1075048		48"	710 lbs

## BLH7PS5 blocked plate mount fifth wheels (Tilt/No-Tilt Option)

**Part Number Mounted Height\* Description**  
 BLH7PS58375 . . . 8-3/8" . . . Blocked H7 top plate with Blocked PS5 bracket  
 BLH7PS59375 . . . 9-3/8" . . . Blocked H7 top plate with Blocked PS5 bracket  
 BLH7PS510375 . . 10-3/8" . . . Blocked H7 top plate with Blocked PS5 bracket

Removing blocking bar converts "No-Tilt" blocked fifth wheel to standard fifth wheel that can tilt.

Mount	Description	Width x length	Holes per side	Hole spacing across frame	First hole measured from rear, then spacing between holes
BLPS5	Plate short	40.00" x 23.75"	5 (for 5/8" hardware)	38"	1.88", 6.00" - 4.00" - 4.00" - 6.00"



## Kits and parts for blocked fifth wheels

### Blocking Kits (For AWB Brackets)

Blocking kit for H5092 top plate and BLHAWB bracket. . . . . KIT-BLK-SLD

Note: The bracket height must be 8 3/4" for AWB. Kit must be installed by a certified welder. See TB-030 for installation instructions.

### Replacement Bar (For AWB and PS5 Brackets)

Replacement bar for Blocked H5092 and H7 top plate. . . . . BAR-396-BK  
 (For BLHAWB, BLHMWS and BLHPSA brackets)

